

# Mini VersaPar

7x10W RGBW compact zoom PAR  
ORDER CODE: **MINIVERSAPAR**



Mini **VersaPar** is a compact indoor LED zoom PAR designed for rental companies. The multi-purpose concept combining high brightness, wide zoom range and advanced colour mixing truly makes this a unique fixture. Mini VersaPar is equipped with 10° - 40° unrivalled zoom range, high efficiency, perfect chromatic uniformity, HD dimming technology and totally silent operation.

## MAIN FEATURES

- 7x10W RGBW/FC LED
- Wide zoom range from 10° - 40° (1:4 zoom)
- Silent operation for studio application

## TECHNICAL SPECIFICATION

### LIGHT SOURCE

- Source: 7x10W RGBW LEDs
- Luminous flux: (10°) 1'012 lm - (40°) 1'335lm
- Lux: (10°) 4'415 lx - (40°) 378lx @3 m
- Source life expectancy: > 50.000 h

### OPTICS

- Zoom: 10° - 40° motorised linear zoom
- Lens type: honeycomb gapless plano-convex optics

### COLOUR SYSTEM

- Colour mixing: RGBW / FC
- White presets: 2.800 K - 10.000K
- Colour wheel: virtual colour wheel with macros
- Macros: several pre-built pixel macros with adjustable speed

### DYNAMIC EFFECTS

- Static mode: selection of static colour
- Manual mode: manual adjustment of colour
- Auto mode: built-in programs with execution speed adjustment
- Sound mode: music activation through internal microphone and sensitivity control

### BODY

- Body: sturdy die-cast aluminium body
- Body colour: black

### CONTROL

- Protocols: DMX512
- DMX channels: 5 / 7 / 10channel
- W-DMX: optional, proprietary protocol compatible with WIFIBOX, WDBOX
- Display: 4 chars display
- Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included
- Master/Slave: for synchronised operation of more units linked in a chain

### ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Dimmer curves: selectable dimming modes available
- Strobe / shutter: 1 / 28 Hz, electronic
- Operating temperature: -10° ~ +40°
- LED Control: flicker free operation

### ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 69,2W
- Max power consumption (at 120V): 70W
- Output (at 230V): 54 units on a single power line
- Output (at 120V): 11 units on a single power line

### PHYSICAL

- IP rating: 30 with a protective vent to prevent condensation, dust, compensate pressure
- Cooling: active, silent operation
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p + 5p IN/OUT connectors
- Power connection: Seetronic powerCON IN/OUT connectors
- Dimensions (WxHxD): 235xx301x223mm
- Weight: 3,7kg

## ACCESSORIES & RELATED PRODUCTS

▪ 9313FCAL03	Ass. 3x2.5mm TH07 cable, 16A 3p 230V CEE plug, SETSAC3FCA socket, L.3 m	▪ TOUR53413L03	Dmx cable HC5340. CANC3MXX XLR 3p->CANC3FXX XLR (f) 3p, L.3m
▪ 9333FCAL03	Ass. 3x2.5mm TH07 cable, SHUKO plug, SETSAC3FCA socket, L.3 m	▪ TOUR53415L03	Dmx cable HC5340. CANC5MXX XLR 5p->CANC5FXX XLR (f) 5p, L.3m
▪ 938025L03	3x2.5mm TH07 Cable, 20A SETSAC3FCA, 20A SETSAC3FCB, L. 3m	▪ WIFIBOX	DMX controller interface, Wi-Fi/DMX IN, Wi-Fi / DMX OUT
▪ C6002B	Slim aluminum clamp, 200kg loading, 48-51mm tubes, M10 bolt, Black	▪ WDBOX	Wireless DMX Transceiver, IN/OUT 3-pin XLR, distance 200m, 2.4 GHz, 0.6 kg
▪ RSR0630B	Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black	▪ WIFIUSB	USB Wi-Fi transceiver, compatible with WIFIBOX and WDBOX
		▪ UPBOX1U	Firmware uploader kit, USB IN, 3pin XLR DMX OUT, USB OUT