

DisplayCob WW

45W compact Tungsten White COB Par with parabolic reflector

ORDER CODE: **DISPLAYCOBWW**



DisplayCob WW is the compact version of the popular StudioCob WW - perfect for an installation or indoor venues. DisplayCob WW employs a 45 W COB LED source tungsten white 3.200 K, combined with a special parabolic reflector built in aluminium which develops an extremely bright and homogeneous output of 96 CRI and interchangeable lens systems to switch from 60° (incl.) to 30° (incl.) and 15° (opt.).

MAIN FEATURES

- Compact LED PAR with high CRI 45W Warm White COB source
- HD dimming and an extensive and even colour palette
- Flexible lens options of 15° - 30° - 60° and functional barn doors

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source: 45W White COB LED
- CCT: 3.200K
- Luminous flux: (30°) 2'171 - (60°) 2'309lm @full
- Lux: (30°) 236lx @5 m full
- Lux: (60°) lx
- CRI: >96
- R9: >82
- TLCI: >97
- TM30 Rf: >94
- TM30 Rg: 100
- Source life expectancy: > 30.000 h

OPTICS

- Beam angle: 60°
- Field angle: 80°
- Lens type: parabolic reflector in combination with HD fresnel lens
- Additional optics: 30° (incl) - 15° (opt)

DYNAMIC EFFECTS

- Static mode: selection of static colour
- Manual mode: manual adjustment of dimmer and strobe
- Auto mode: built-in programs with execution speed adjustment

BODY

- Body: sturdy die-cast aluminium body
- Body colour: black

CONTROL

- Protocols: DMX512
- DMX channels: 1 / 2 / 5channel
- Display: Graphic User Interface
- Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included
- Master/Slave: for synchronised operation of more units linked in a chain

ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Dimmer curves: 4 selectable dimming modes available
- Strobe / shutter: 1 - 28 Hz, electronic
- Operating temperature: -10° ~ +45°
- LED Control: flicker free operation
- Selectable PWM: 600 ~ 25.000 Hz

ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 52W
- Power factor: >0,98

PHYSICAL

- IP rating: 20
- Cooling: passive cooling and fan-free
- Suspension and fixing: double hanging bracket suitable for safe hanging and for floor positioning
- Signal connection: XLR 5p IN/OUT connectors
- Power connection: moulded IP power IN connector
- Dimensions (WxHxD): 166x118x250mm
- Weight: 1,85kg


ACCESSORIES & RELATED PRODUCTS

- | | |
|-----------------|---|
| ▪ C6002B | Slim aluminum clamp, 200kg loading, 48-51mm tubes, M10 bolt, Black |
| ▪ DISPLAYCOBL30 | Optics for DISPLAYCOB projectors series, 30° |
| ▪ RSR0630B | Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black |
| ▪ TOUR53415L03 | Dmx cable HC5340. CANC5MXX XLR 5p->CANC5FXX XLR (f) 5p, L.3m |

- | | |
|-------------------|---|
| ▪ DISPLAYCOBL15 | Optics for DISPLAYCOB projectors series, 15° |
| ▪ DISPLAYCOBDBDK | Barn door with 4 directional flaps to adjust the light beam, for DISPLAYCOB, BK |
| ▪ DISPLAYCOBTGPBK | Filter frame for DISPLAYCOB projectors, black |
| ▪ UPBOX1U | Firmware uploader kit, USB IN, 3pin XLR DMX OUT, USB OUT |


PRESET FULL ON

Beam angle 50%: 30°




PRESET FULL ON

Beam angle 50%: 30°



TECHNICAL DRAWINGS



For more product
info and downloads
visit our website



PROLIGHTS is a trademark of
MUSIC & LIGHTS S.r.l.
musiclights.it

Via A. Olivetti snc
04026 - Minturno (LT) ITALY
Tel: +39 0771 72190

prolights.it
info@prolights.it