

Z 8Strip

Battery operated LED pixel batten

ORDER CODE: **Z8STRIP**



Z 8Strip is a new generation battery operated fixture that marks a new step in wireless lighting technology, being one of the brightest portable fixtures in the event industry. **Z 8Strip** is encased in IP65 rated housing allowing it to meet any working condition. Featuring 8x10 W high-power RGBW full colour CREE LEDs pixel controlled to achieve high brightness and can also a favourite for temporary architectural installations. **Z 8Strip** is equipped with a lithium battery pack allowing it to be left out for up to 16 hours (colour-changing) and W-DMX control for full cable-free operations.

MAIN FEATURES

- Huge light output from a battery luminaire with 8x10 W CREE XML RGBW LEDs
- Wireless DMX control, 8 hours battery life on full white and IP65 rating for incredible versatility
- On-board mains and DMX connectors for standard use

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source: 8x10W RGBW LEDs
- Luminous flux: 1'064lm
- Lux: 4'600lx @3 m full
- Source life expectancy: > 50.000 h

OPTICS

- Beam angle: 10°
- Field angle: 21°
- Other: magnetic holder for diffusion filters or gels

COLOUR SYSTEM

- Colour mixing: RGBW / FC
- White presets: 3.200 K ~10.000K
- Colour wheel: virtual colour wheel with macros
- Macros: built-in white presets

DYNAMIC EFFECTS

- Static mode: selection of static colour
- Manual mode: manual adjustment of colour
- Auto mode: built-in programs with execution speed adjustment

BODY

- Body: sturdy die-cast aluminium body
- Body colour: black

CONTROL

- Protocols: DMX512, W-DMX
- DMX channels: 4 / 6 / 10 / 32 / 37channel
- Pixel control: pixel2pixel control
- W-DMX: included, wireless solution receiver
- Display: black OLED touch display
- Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included
- Master/Slave: for synchronised operation of more units linked in a chain

ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Dimmer curves: 4 selectable dimming modes available
- Strobe / shutter: 1 - 25 Hz, electronic
- Operating temperature: 0° ~ +35°
- LED Control: flicker free operation

ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz

BATTERY

- Battery: 14,8V lithium
- Estimated battery life in colour change mode up to: 16h
- Estimated battery life in single colour mode up to: R: 16 h - G: 12,5 h - B: 13 h - W: 13h
- Estimated battery life in full-mode up to: 6h
- Re-charge connection: power cable
- Re-charge time: 5h/max
- Battery status: shown on display

PHYSICAL

- IP rating: for temporary outdoor installation - IP65 (front) - IP54 (bottom)
- Cooling: passive cooling and fan-free
- Suspension and fixing: bracket for hanging and positioning
- Signal connection: Seetronic XLR 5p IN/OUT connectors
- Data connection: W-DMX receiver
- Power connection: Seetronic powerCON waterproof IN/OUT connectors
- Dimensions (WxHxD): 801x216x153mm
- Weight: 10kg

ACCESSORIES & RELATED PRODUCTS

▪ 9313FXWL03	Ass. 3x2.5mm TH07 cable, 16A 3p 230V CEE plug, SETSAC3FX socket, L.3 m
▪ 9333FXWL03	Ass. 3x2.5mm TH07 cable, SHUKO plug, SETSAC3FX socket, L.3m
▪ 938225L03	3x2.5mm TH07 Cable, 16A SETSAC3MX, 16A SETSAC3FX, L. 3m
▪ C6002B	Slim aluminum clamp, 200kg loading, 48-51mm tubes, M10 bolt, Black
▪ INF53415L03	Dmx cable HC5340. SETMC5MXXB XLR 5p->SETMC5FXXB XLR (f) 5p L.3m
▪ RSR0630B	Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black
▪ WSBBF1G5	BlackBox F-1 G5 transmitter, 2,45GHz & 5.2/5,8 GHz, DMX/ RDM, 512Ch
▪ WSBBF1G6	BlackBox F-1 G6 transrec, 512ch, 2.45GHz, DMX&RDM,Bluetooth,G3,G4,G4S, G5, CRMX

▪ WSBBR512G5	BlackBox R-512 G5 receiver 512Ch, 2.45GHz & 5.8GHz, DMX/RDM optional
▪ WSBBR512G6	BlackBox R-512 G6 receiver 512Ch, 2.45GHz,DMX&RDM,BIuetooth,G3,G4,G4S,G5,CRMX
▪ FCLZ8STRIP	Flight case for 6 Z8STRIP, 1000x802x600 mm, 46 kg
▪ UPBOX1U	Firmware uploader kit, USB IN, 3pin XLR DMX OUT, USB OUT
▪ FILTERROLLF2	Frost Dif. filter Roll 7600x1220mm
▪ ARCLUMIL15D45	Optic lens 15°, D.45mm
▪ ARCLUMIL25D45	Optic lens 25°, D.45mm
▪ ARCLUMIL40D45	Optic lens 40°, D.45mm
▪ FCLZ8STRIPE	Flight case for 6 Z8STRIP,
▪ WDBBOX	WDMX battery transmitter, mini 5p DMX and WIFI IN, 2.4 GHz, 0.4 kg