



# grandMA3 onPC command wing

Art.-No. 4010511



When we talk about onPC solutions, we talk about mobility, flexibility and affordable prices - all combined in the grandMA3 onPC command wing! It is your mobile control solution for the grandMA3 onPC software.

You have a computer or laptop with the grandMA3 onPC software installed? Then simply connect your onPC wing via USB and you are ready for programming. The command area looks the same as on the grandMA3 consoles including the five dual-encoders and 40 separate playbacks to directly control 4 096 parameters.

You have three DMX ports available, and you can use Ethernet protocols to send DMX data. On the rear panel you find all inputs and outputs of a grandMA3 console. MIDI, timecode and remote control are directly available. So you get the real console feeling!

The grandMA3 onPC command wing is designed as a powerful control solution on tour, for smaller theaters, shows, clubs or houses of worship. Also, if you are looking for a clever backup solution for your grandMA3 system or if you need a small pre-programming station, the grandMA3 onPC command wing will be the perfect choice.



## Features

- onPC wing for real-time control of 4 096 parameters in combination with grandMA3 onPC
- Command section similar to grandMA3 compact layout
- 29 rotary RGB backlit encoder
- 5 dual encoders
- 10 motorized 60 mm faders
- 40 separate playbacks
- 16 assignable x-keys
- 2 motorized A/B faders 100 mm
- 1 Level-Wheel
- Individually backlit and dimmable silent (clickless) keys
- Just connect via USB to any PC running grandMA3 onPC

## Scope of delivery

| Art.-No. | Article                                                        | Quantity |
|----------|----------------------------------------------------------------|----------|
| 4011454  | Dust cover grandMA3 onPC command wing / XT                     | 1        |
| 4021426  | MA cable USB 2.0, type A to type B, length 2.0m                | 1        |
| 4011387  | MA Magnetic plate for easy labeling of 10 faders, for grandMA3 | 1        |
| 4023136  | MA Quick Manual for grandMA3 onPC command wing                 | 1        |

1 x MA power cable, IEC-C plug (lockable), length 2.0 m, open end

## Technical Specifications

|                                          |                                                                                                                                                                                                                                                                                                                                                        |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Parameters</b>                        | 4 096 (HTP/LTP)                                                                                                                                                                                                                                                                                                                                        |
| <b>Parameters Mode2</b>                  | not applicable (no Mode2)                                                                                                                                                                                                                                                                                                                              |
| <b>Operating voltage/ Supply voltage</b> | AC 100 - 240 V; 50/60 Hz                                                                                                                                                                                                                                                                                                                               |
| <b>Power</b>                             | max. 50 VA                                                                                                                                                                                                                                                                                                                                             |
| <b>Operating Temperature</b>             | 0 °C up to 40 °C / 32 °F up to 104 °F                                                                                                                                                                                                                                                                                                                  |
| <b>Dimensions</b>                        | 620 x 427 x 102 mm / 25 x 17 x 4 in<br>(width x depth x height)                                                                                                                                                                                                                                                                                        |
| <b>Net weight</b>                        | 10 kg / 22 lbs                                                                                                                                                                                                                                                                                                                                         |
| <b>Connectors</b>                        | 1 x IEC-60320 C14 cord<br>2 x DMX512-A Out (5pin XLR female)<br>1 x DMX512-A In (5pin XLR male)<br>1 x MIDI In (5pin DIN female)<br>1 x MIDI Out (5pin DIN female)<br>1 x Linear Timecode (3pin XLR female)<br>1 x GPI General Purpose Interface (D-SUB DE9 female) for remote control<br>1 x USB 2.0 (type B)<br>1 x LED desk light (4pin XLR female) |

## Article

| Art.-No. | Article                    |
|----------|----------------------------|
| 4010511  | grandMA3 onPC command wing |



## Accessories

| Art.-No. | Article                                                                         |
|----------|---------------------------------------------------------------------------------|
| 4023468  | MA Case grandMA3 onPC command wing, (by Peli)                                   |
| 4022579  | MA Case grandMA3 onPC command wing, (by Amptown)                                |
| 4023575  | grandMA3 onPC fader wing                                                        |
| 4011080  | MA LED desk light grandMA3, straight plug XLR 4pin, length 27", including cover |
| 4011081  | MA dust cover for LED desk light, 27"                                           |

## More product pictures

